



# Submittal Data

MODEL  
**BG-123P**

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

### PERFORMANCE DATA

Power supply 1Ph,230/208V,60Hz

#### Cooling

Capacity	Btu/h	12000/11700
Input	W	1142/ 1114
Rated current	A	5.2/5.6
EER	Btu/w	10.5
CEER	Btu/w	10.5

#### Heating

Capacity	Btu/h	NA
RATED Input(Heater)	W	NA
Rated current	A	NA
Max. Current	A	NA

#### Compressor Electrical

Model	ASM103N11VEZ	
Type	ROTARY	
Brand	GMCC	
Capacity	Btu/h	12096
Input	W	820
Rated current(RLA)	A	3.95
Thermal protector	NA	
Refrigerant oil/oil charge	oz.	ESTEL OIL RB68 10.14
Refrigerant type	oz	R410A/21.87

#### Air flow & Noise level

Indoor air flow	CFM	286/264/240
Indoor noise level	dB(A)	60.5/59.1/56.5
Outdoor air flow	CFM	420/390/350
Outdoor noise level	dB(A)	68.5/66.7/64.4
Window Opening	Max Width	NA
	Max Heigt	NA

#### Accessories

Wall Sleeve-breakdown	EA448F
-----------------------	--------



#### Fan Motor

Model	YKTS-100-4-52	
Input	W	175/160/144
Speed	RPM	1460/1380/1280

#### Dimensional Data


Dimension(W*D*H)	inch	24.2x20.3x14.5
Packing (W*D*H)	inch	28x26.6x16.9
Net/Gross weight	lbs.	78.1/89.1

#### SYSTEM DATA


Design pressure	PSIG	300/520
Thermostat type	Remote Controller	
Application area (Cooling EPA)	450-550	

#### Cord and Plug


Cord Length	ft.	6.5
Plug Face	Nema	6-15P




15A-115V  
NEMA 5-15P



15A-230V  
NEMA 6-15P



20A-230V  
NEMA 6-20P



30A-230V  
NEMA 6-30P